



COME TO GRIPS

WITH GREATER PRODUCTIVITY

When you need to pick up large, heavy objects, grab bucketfuls of debris and clear away brush quickly, get a tighter grip on productivity with AMI's Graptor Bucket and Graptor Rake. Powered by a helical actuator, the Graptor Bucket and Graptor Rake feature incredible holding strength. The built-in rotary actuated thumb gives operators improved flexibility and precision by maintaining constant grip on the load throughout the bucket's entire rotation. Neatly integrated into the top crossbar of the Graptor, the actuator produces up to 54,000 foot-pounds of torque at 3,000 psi – putting out the most torque in the most compact design - making the Graptor a powerful tool that keeps a tight handle on heavy, bulky loads.










Graptor Rake



Confidently handle heavy and awkward loads with the superior grip of the Graptor's integrated thumb. For demolition work requiring picking, sorting and transferring, the Graptor strongly grips the load and holds it securely throughout the full rotation of the bucket, all the way to roll out. The Graptor also takes out the guesswork of trying to control both thumb and bucket at the same time, providing a safer worksite and reducing hydraulic line failure from over-pressure.





HELICAL ACTUATOR

Designed for strength and durability, the Graptor is powered using a helical actuator fitted into the crossbar. With holding strength up to 54,000 ft.lbs of torque at 3,000 PSI, the actuator's tidy design eliminates the need for bulky hydraulic cylinders.



HEAVY DUTY CONSTRUCTION

Aggressive serrated side bars, welded in place come standard for maximum grip.

Replaceable side cutters are available for more abrasive applications

The Graptor is built using low wearing AR400 steel.





With no cylinders and no exposed hydraulics, you don't have to worry about rocks or debris causing damage.



	AMI GRAPTUR BUCKET SPECIFICATIONS CHART						
MODEL	Ex. Weight (x 1000)	Bucket Width	Capacity	Teeth Quantity	Thumb Tines	Weight	
GRHD1012E24	10 - 12 lbs	24 in	4.50 CU FT	5	4	480 lbs	
GRHD1214E24	12 - 14 lbs	24 in	8.00 CU FT	5	4	570 lbs	
GRHD1416E24	14 - 16 lbs	24 in	0.290 CU YD	4	3	825 lbs	
GRHD1416E30	14 - 16 lbs	30 in	0.388 CU YD	5	4	880 lbs	
GRHD2433E24	24 - 33 lbs	24 in	0.412 CU YD	4	3	1200 lbs	
GRHD2433E30	24 - 33 lbs	30 in	0.55 CU YD	4	3	1475 lbs	
GRHD3340E30	33 - 45 lbs	30 in	0.625 CU YD	4	3	1800 lbs	
GRHD3340E36	33 - 45 lbs	36 in	0.813 CU YD	5	4	2000 lbs	
GRHD3340E42	33 - 45 lbs	42 in	1.000 CU YD	5	4	2150 lbs	
GRHD4045E36	45 - 55 lbs	36 in	0.875 CU YD	5	4	2650 lbs	
GRHD4045E42	45 - 55 lbs	42 in	1.063 CU YD	5	4	2800 lbs	
GRHD4045E48	45 - 55 lbs	48 in	1.250 CU YD	6	5	3275 lbs	
GRHD4560E36	55 - 65 lbs	36 in	1.063 CU YD	4	3	2840 lbs	
GRHD4560E42	55 - 65 lbs	42 in	1.188 CU YD	5	4	3090 lbs	
GRHD4560E48	55 - 65 lbs	48 in	1.375 CU YD	5	4	3270 lbs	
GRHD4560E54	55 - 65 lbs	54 in	1.500 CU YD	5	4	3520 lbs	
GRHD6080E42	65 - 90 lbs	42 in	1.563 CU YD	4	3	4600 lbs	
GRHD6080E48	65 - 90 lbs	48 in	1.875 CU YD	5	4	4800 lbs	
GRHD6080E54	65 - 90 lbs	54 in	2.125 CU YD	5	4	5280 lbs	

AMI RAKE SPECIFICATIONS CHART							
MODEL	Ex. Weight (x 1000)	Rake Width	Rake Tine Quantity	Thumb Tine Quantity			
GRRR1416E48	14 - 16 lbs	48 in	4	3			
GRRR2433E54	24 - 33 lbs	54 in	5	2			
GRRR3340E60	33 - 45 lbs	60 in	6	3			
GRRR4045E60	45 - 55 lbs	60 in	6	3			
GRRR4560E72	55 - 65 lbs	72 in	6	3			
GRRR6080E72	65 - 90 lbs	72 in	6	3			









www.youtube.com/AMIAttachments











Phone: (519) 699-0387 Fax: (519) 699-0440 1270 Geddes St., Hawkesville, ON, Canada NOB 1X0 www.amiattachments.com





